

KORO-MAT™

Switchboard Matting – ASTM Tested

PERFORMANCE

Tested to ASTM D178/ ANSI J6.7, Type II	Class 2 - 1/4" Thickness	Class 1 - 3/16" Thickness
Dielectric Test Voltage	30,000 VAC	20,000 VAC
Proof Tested Over Entire Surface at Recommended Maximum Use Voltage	20,000 VAC	10,000 VAC
	17,000 VAC	7,500 VAC
Ozone Resistance	No Visible Effect	No Visible Effect
Flame Resistance	Self Extinguishing	Self Extinguishing
Oil Resistance	No Visible Effect	No Visible Effect

CORRUGATED - BLACK

Size	Pounds Per Yard	Pounds Per Roll	Product Number
1/4" x 24" x 25 yards	10.5	262	39-44-4750-003
1/4" x 36" x 25 yards	16.0	400	39-44-4740-003
1/4" x 48" x 25 yards	21.0	525	27-88-7520-003
3/16" x 24" x 25 yards	7.8	195	39-44-7700-003
3/16" x 36" x 25 yards	11.8	295	39-44-7720-003

DECKPLATE - BLACK

Size	Pounds Per Yard	Pounds Per Roll	Product Number
1/4" x 24" x 25 yards	10.5	262	39-44-4755-983
1/4" x 36" x 25 yards	16.0	400	39-44-4745-983
1/4" x 48" x 25 yards	21.0	525	27-88-7450-983

DECKPLATE – BLACK / YELLOW BORDER

Size	Pounds Per Yard	Pounds Per Roll	Product Number
1/4" x 36" x 25 yards	16.0	400	39-44-4746-983

Please contact us for additional technical information

Profusion Industries
 822 Kumho Dr. Fairlawn, OH 44333
 Tel: 800 938-2858
Info@ProFusionIndustries.com
www.KoroMat.com